



POLY-CRYSTALLINE SOLAR MODULE - 60 CELLS

OS75P

OS85P

FEATURES

- High reliability with guaranteed 0 to +5W power output tolerance
- Passing mechanical load test of 5400 Pa to withstand heavier snow load and 2400 Pa to withstand wind pressure
- Strong frame, easy to install
- High transparency tempered glass: 3.2 mm, with durable glass surface
- Excellent performance under low light environment
- International quality and safety certifications

WARRANTIES

- 10 years limited product warranty
- 5 years at 95% of the minimal rated power output
- 10 years at 90% of the minimal rated power output
- 18 years at 85% of the minimal rated power output
- 25 years at 80% of the minimal rated power output





ELECTRICAL CHARACTERISTICS	OS75P	OS85P
Nominal Output (pmax) [W]	75	85
Flash Test Power Classification [W]	0 / +5	0 / +5
Voltage at Pmax (Vmp) [V]	17.76	17.78
Current at Pmax (Imp) [A]	4.223	4.781
Open Circuit Voltage (Voc) [V]	21.312	21.336
Short Circuit Current (Isc) [A]	4.729	5.354
Cell Efficiency [%]	13.77	15.6
Module Efficiency [%]	11.7	13.3

STC* (Standard Test Condition): Irradiance 1000W/m², Module Temperature 25°C, Air

TEMPERATURE CHARACTERISTICS	
NOCT**	45±2 °C
Temperature Coefficient of Pmax	-0.47 %/°C
Temperature Coefficient of Voc	-0.346 %/°C
Temperature Coefficient of Isc	0.036 %/°C
Operating Temperature	-40 °C to +85 °C

NOCT**: Nominal Operation Cell Temperature Sun 800W/m²; Air 20°C; Wind speed 1m/s

MECHANICAL CHARACTERISTICS		DIMENSIONS
Solar Cells	36(4x9) polycrystalline cells 156x97 mm	
Font Cover	3.2 mm thick, low iron tempered glass	
Back Cover	TPT (Tedlar-PET-Tedlar)	
Encapsulant	EVA (Ethylene vinyl acetate)	
Frame	Anodized aluminium alloy, double wall	
Diodes	3 Bypass diodes serviceable	
Junction Box	IP65 rated	
Connector	MC4 or compatible connector	
Cables	Length: 950 mm / Section: 4.0 mm ²	
Dimensions	951 x 674 x 35 mm	
Weight	5.4 kg	
Max. Load	Certified to 2400 Pa	

Oviera Solar reserves the right to make specifications changes without any prior notice.
 This data sheet complies with the EN 50380 requirements
 July 2012 Oviera Solar Srl. All rights reserved.

